

REVERSE OSMOSIS WATER FILTER

WRO-150

4 STAGES RO FILTRATION - 150GPD

WRO-150 is reverse osmosis filtration station able to treat up to 150GPD (52lb/h) [23l/h] of water. It will remove 95% of the dissolved solids contained in water.

4 stages filtration:

- **1st stage:** 5 micron PP
- **2nd & 3rd stage:** Carbon filter
- **4th stage:** 2 RO membranes

Cartridges size: 20in

Inlet & outlet diam.:

1/2in NPT

Max pressure:

80PSI [550kPa]

Storage tank:

5Gal [19l]



WRO-200

4 STAGES RO FILTRATION - 200GPD

WRO-200 is reverse osmosis filtration station able to treat up to 200GPD (69lb/h) [31l/h] of water. It will remove 95% of the dissolved solids contained in water.

4 stages filtration:

- **1st stage:** 5 micron PP
- **2nd & 3rd stage:** Carbon filter
- **4th stage:** 2 RO membranes

Cartridges size: 20in

Inlet & outlet diam.:

1/2in NPT

Max pressure:

80PSI [550kPa]

Storage tank:

10Gal [38l]



WRO-400

4 STAGES RO FILTRATION - 400GPD

WRO-400 is reverse osmosis filtration station able to treat up to 400GPD (139lb/h) [63l/h] of water. It will remove 95% of the dissolved solids contained in water.

4 stages filtration:

- **1st stage:** 5 micron PP
- **2nd & 3rd stage:** Carbon filter
- **4th stage:** 2 RO membranes

Cartridges size: 20in

Inlet & outlet diam.:

1/2in NPT

Max pressure:

80PSI [550kPa]

Storage tank:

20Gal [76l]

